

WL-C-0X Chemical protective coverall - Type 5/6
WL-CB-0X Personal Protective Equipment Cat.III

FEATURES & BENEFITS

- **Ultra-breathable material with ergonomic design:** reduces heat stress for enhanced working comfort, even in demanding conditions.
- **Integrated elastics** (hood, waist, ankles): ensure an optimal fit to help limit ingress and improve overall protection.
- **Two-way zipper with adhesive storm flap:** enables quick donning and doffing while ensuring maximum protection against contaminants.
- **Jersey cuffs:** soft contact with the skin, reducing irritation and improving comfort during extended wear.
- **3-pieces hood and raglan sleeves:** provide excellent freedom of movement, ideal for tasks requiring precision and mobility.

Recommended use

- Woodworking and construction trades
- Composites industry/Industrial cleaning and maintenance
- Sanding, insulation, servicing and maintenance work
- Dirty environments, hygiene applications and factory visits



Item	Color
WL-C-0X	<input type="checkbox"/> White
WL-CB-0X	<input type="checkbox"/> Blue

PRODUCT DETAILS

Product name :	WeeCover
Product type :	Type 5/6
Material :	SMS
Grammage :	55 g/m ²
Construction :	Elasticated waist, ankles and 3-pieces hood Double way zipper Protective flap with adhesive Jersey cuffs
Seams :	4 threads overstitched
Qty per case :	50 units
Origin :	China

CERTIFICATIONS & STANDARDS

- Complies with the requirements of Regulation (EU) 2016/425 on Personal Protective Equipment
- Manufactured under an ISO 9001 certified system

COVERALL TESTS PERFORMANCES

	Standard / Test method	Results
Type 5 inward leakage test for solid aerosol particles	EN ISO 13982-1:2004 + A1:2010	Compliant
Type 6 low-density spray test	EN 13034:2005 + A1:2009	Compliant
Protection against solid radioactive particles	EN 1073-2:2002	Class 1
Electrostatic protection with grounding	EN 1149-5:2018	Compliant
Seam strength	EN ISO 13935-2	Class 3/6

PHYSICAL PROPERTIES OF THE FABRIC

Tests	Test method	Class
Abrasion resistance	EN 530	Class 2/6
Flex cracking resistance	ISO 7854 B	Class 6/6
Tear resistance	ISO 9073-4	Class 2/6
Tensile strength	ISO 13934-1	Class 1/6
Puncture resistance	EN 863	Class 1/6
Resistance to ignition	EN 13274-4	Compliant

FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530

Chemicals tested	Penetration	Repellency
Sulphuric Acid 30%	Class 3/3	Class 2/3
Sodium Hydroxide 10%	Class 3/3	Class 2/3

STORAGE CONDITIONS

Normal storage and conservation conditions: Should not be exposed to moisture and sunlight, and should be stored at room temperature.

Product shelf life: 5 years

LOGISTICS



Outer case spec.

Item	Size	Size mm	Gross weight (kg)	QTY/ palett
WL-C-01	S			
WL-C-02	M			
WL-C-03	L			
WL-C-04	XL			
WL-C-05	XXL			
WL-C-06	XXXL			
WL-C-01	S	450 x 280 x 640	11	13
WL-CB-02	M			
WL-CB-03	L			
WL-CB-04	XL			
WL-CB-05	XXL			
WL-CB-06	XXXL			

Inner bag spec.

Size mm	Gross weight (g)	Pack.
320 x 220 x 20	200	50 x 1

 **EAN Code**

Item	Outer case	Inner bag	Item	Outer case	Inner bag
WL-C-01	3 701 407 401 397	3 701 407 401 403	WL-CB-01	3 701 407 401 380	3 701 407 401 410
WL-C-02	3 701 012 800 035	3 701 012 800 028	WL-CB-02	3 701 012 800 315	3 701 012 800 608
WL-C-03	3 701 012 800 059	3 701 012 800 042	WL-CB-03	3 701 012 800 639	3 701 012 800 622
WL-C-04	3 701 012 800 073	3 701 012 800 066	WL-CB-04	3 701 012 800 653	3 701 012 800 646
WL-C-05	3 701 012 800 097	3 701 012 800 080	WL-CB-05	3 701 012 800 677	3 701 012 800 660
WL-C-06	3 701 012 800 110	3 701 012 800 103	WL-CB-06	3 701 012 800 448	3 701 012 800 431