

**WL-ME-00**

**Chemical protective sleeve - Type PB 6B**  
Personal Protective Equipment Cat.III

## FEATURES & BENEFITS

- Liquid splash-resistant and lint-free material to prevent contamination in controlled areas.
- Tunneled elastics with bound seams provide enhanced wrist protection and help limit environmental contamination.
- Antistatic treatment on both sides facilitates the dissipation of electrostatic charges.
- Elasticated thumb loop for excellent hold.
- Length: 50 cm



## PRODUCT DETAILS

Product name :	<b>Weepro sleeve</b>
Product type :	Type PB 6B
Fabric :	Microporous film
Grammage :	63 g/m <sup>2</sup>
Confection :	Sleeve with elastics at both ends Elasticated thumb loops
Coutures :	4-thread overlock stitching
Color :	White
Qty / case :	10 polybags of 20 sleeves
Origin :	China

## CERTIFICATIONS & STANDARDS

- Complies with the requirements of Regulation (EU) 2016/425 on Personal Protective Equipment
- Manufactured under an ISO 9001 certified system

PHYSICAL PROPERTIES OF THE FABRIC		
Tests	Test method	Results
Abrasion resistance	EN 530	Classe 1/6
Flex cracking resistance	ISO 7854 B	Classe 4/6
Tear resistance	ISO 9073-4	Classe 2/6
Tensile strength	ISO 13934-1	Classe 1/6
Puncture resistance	EN 863	Classe 1/6
Seam strength	EN ISO 13935-2	Classe 3/6

### FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530

Chemicals tested	Penetration	Repellency
Sulphuric Acid 30%	Classe 3/3	Classe 3/3
Sodium Hydroxide 10%	Classe 3/3	Classe 3/3
O-Xylene	Classe 3/3	Classe 2/3
Butan-1-ol	Classe 3/3	Classe 3/3

### FABRIC RESISTANCE TO PENETRATION BY INFECTIVE AGENTS EN 14126

Resistance to penetration by contaminated liquids under hydrostatic pressure ISO 16604 / ISO 16603	Classe 6/6
Resistance to penetration by contaminated liquids according to EN ISO 22610	Classe 6/6
Resistance to penetration by contaminated liquid aerosols according to EN ISO 22611	Classe 3/3
Resistance to penetration by contaminated solid particles ISO 22612	Classe 3/3

## STORAGE CONDITIONS

Normal storage and conservation conditions: Should not be exposed to moisture and sunlight, and should be stored at room temperature.

## LOGISTICS



### Outer case Spec.

Item	Size	Gross weight (kg)	Qty / pallet
WL-ME-00	520 x 250 x 220	4,5	50

### Inner bag Spec.

Packaging
10 polybags x 20 unis

### Ean code

Item	Case
WL-ME-00	3 701 012 801 322