

## WL-C1-0x Chemical protective coverall - Type 5/6

### WL-C0-0xl Personal Protective Equipment Cat.III

### FEATURES & BENEFITS

- **Ultra-breathable material with an ergonomic design:** reduces heat stress for enhanced working comfort, even in demanding conditions.
- **Integrated elasticated hood, waist, and ankles:** ensures an optimal fit, helping to limit ingress and improve overall protection.
- **Two-way zipper with adhesive storm flap:** allows quick donning and doffing while ensuring maximum sealing against contaminants.
- **Three-piece hood and raglan sleeves:** provide excellent freedom of movement, ideal for tasks requiring precision and mobility.
- **Full-body design with integrated boot covers and anti-slip sole:** ensures continuous protection and reduces the risk of contamination ingress around the feet.



### Recommended Uses

- Asbestos abatement and remediation
- Asbestos sampling and inspection activities
- Asbestos surveying and diagnostic work
- Sanding, insulation, maintenance, and repair operations
- Thermal and acoustic insulation installation
- Pharmaceutical and cosmetics production environments

### PRODUCT DETAILS

Product name :	<b>WeePro Max1 &amp; WeePro Max1 Integral</b>
Product type :	Type 5/6
Material :	SMS
Grammage :	55 g/m <sup>2</sup>
Confection :	Elasticated waist, ankles and 3-pieces hood Thumb loops Double way zipper Protective flap with adhesive
Seams :	Heat-sealed taped
Origin :	China

Item	Design
WL-C1-x	WeeCover Max1
WL-C1-0xl	WeeCover Max1 Intégral

**CERTIFICATIONS & STANDARDS**

- Complies with the requirements of Regulation (EU) 2016/425 on Personal Protective Equipment
- Manufactured under an ISO 9001 certified system

**COVERALL TESTS PERFORMANCES**

	Standard / Test method	Results
Type 5 inward leakage test for solid aerosol particles	EN ISO 13982-1:2004 + A1:2010	Compliant
Type 6 low-density spray test	EN 13034:2005 + A1:2009	Compliant
Protection against solid radioactive particles	EN 1073-2:2002	Class 1
Seam strength	EN ISO 13935-2	Class 3/6

**PHYSICAL PROPERTIES OF THE FABRIC**

Tests	Test method	Class
Abrasion resistance	EN 530	Class 2/6
Flex cracking resistance	ISO 7854 B	Class 6/6
Tear resistance	ISO 9073-4	Class 2/6
Tensile strength	ISO 13934-1	Class 1/6
Puncture resistance	EN 863	Class 1/6
Resistance to ignition	EN 13274-4	Compliant

**FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530**

Chemicals tested	Penetration	Repellency
Sulphuric Acid 30%	Class 3/3	Class 2/3
Sodium Hydroxide 10%	Class 3/3	Class 2/3

**STORAGE CONDITIONS**

Normal storage and conservation conditions: Should not be exposed to moisture and sunlight, and should be stored at room temperature.

Product shelf life: 5 years

**LOGISTICS**



**Outer case spec**

Item	Size	Size mm	Gross weight (kg)	QTY/pallet
WL-C1-03	L			
WL-C1-04	XL			
WL-C1-05	XXL	520 x 320 x 540	12	14
WL-C1-06	XXXL			
WL-C1-03I	L			
WL-C1-04I	XL			
WL-C1-05I	XXL	450 x 360 x 230	6	14
WL-C1-06I	XXXL			

**Inner bag spec**

Size mm	Gross weight (g)	Packaging
320 x 220 x 20	200	50 x 1
390 x 270 x 30	240	20 x 1

 **EAN Code**

Item	Outer case	Iner bag	Item	Outer case	Iner bag
WL-C1-03	3 701 012 800 295	3 701 012 800 288	WL-C1-03I	3 701 407 401 380	3 701 012 800 981
WL-C1-04	3 701 012 800 318	3 701 012 800 301	WL-C1-04I	3 701 012 800 315	3 701 012 801 001
WL-C1-05	3 701 012 800 332	3 701 012 800 325	WL-C1-05I	3 701 012 800 639	3 701 012 801 025
WL-C1-06	3 701 012 800 356	3 701 012 800 349	WL-C1-06I	3 701 012 800 653	3 701 012 801 049