

## WL-CCE/AD

## Chemical protective shoecovers - Type PB6 "B" Personal Protective Equipment Cat.III

### FEATURES & BENEFITS

- Very low-linting fabric preventing contamination in controlled critical environments
- Thick PVC sole with strong anti-slip performance on dry or wet floors
- Elastic bands at the ankle to keep the shoecovers securely in place
- Ideal protection against low-concentration chemical splashes, powders, adhesives, fiberglass, solvents, paints
- Three sizes available: XS, SM & LXL



### Recommended uses

- Pharmaceutical and cosmetic laboratories
- Advanced industries and electronics
- Composites industry
- Food processing industry

Item	Size	Sole length	Sole width
WL-CCE/AD-XS	XS	27 cm	11,5 cm
WL-CCE/AD-SM	SM	30 cm	11,5 cm
WL-CCE/AD-LXL	LXL	36 cm	11,5 cm

### PRODUCT DETAILS

Product name :	<b>WeePro shoecovers</b>
Product type :	Type PB 6
Material :	Microporous film + PVC sole
Material grammage :	63 g/m <sup>2</sup>
Sole grammage :	380 g/m <sup>2</sup>
Confection :	Elasticated at the ankle and heel
Seams :	4 threads overstitched
Color :	White
Qty / case :	400 units
Origin :	China

### CERTIFICATIONS & STANDARDS

- Complies with the requirements of Regulation (EU) 2016/425 on Personal Protective Equipment
- Manufactured under an ISO 9001 certified system

**COVERALL TESTS PERFORMANCES**

	Standard / Test method	Results
Test de pulvérisation à faible densité Type PB 6 "B"	EN 13034:2005 + A1:2009	Compliant
Protection against biological risks	EN 14126:2003 + AC:2004	Compliant
Seam strength	EN ISO 13935-2	Class 3/6

**PHYSICAL PROPERTIES OF THE FABRIC**

Tests	Test method	Results
Abrasion resistance	EN 530	Class 1/6
Flex cracking resistance	ISO 7854 B	Class 4/6
Tear resistance	ISO 9073-4	Class 2/6
Tensile strength	ISO 13934-1	Class 1/6
Puncture resistance	EN 863	Class 1/6

**FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530**

Chemicals tested	Penetration	Repellency
Sulphuric Acid 30%	Class 3/3	Class 3/3
Sodium Hydroxide 10%	Class 3/3	Class 3/3
O-Xylene	Class 3/3	Class 2/3
Butan-1-ol	Class 3/3	Class 3/3

**FABRIC RESISTANCE TO PENETRATION BY INFECTIVE AGENTS EN 14126**

Resistance to penetration by contaminated liquids under hydrostatic pressure ISO 16604 / ISO 16603	Class 6/6
Resistance to penetration by contaminated liquids according to EN ISO 22610	Class 6/6
Resistance to penetration by contaminated liquid aerosols according to EN ISO 22611	Class 3/3
Resistance to penetration by contaminated solid particles ISO 22612	Class 3/3

**STORAGE CONDITIONS**

Normal storage and conservation conditions: Should not be exposed to moisture and sunlight, and should be stored at room temperature.

**LOGISTICS**



**Outer case spec.**

Item	Size	Size Mm	Gross weight (kg)	QTY/pallet
WL-CCE/AD-XS	XS			24
WL-CCE/AD-SM	SM	470 x 320 x 420	11	24
WL-CCE/AD-LXL	LXL			24

**Inner bag spec.**

Cdt
20 x 20 units

 **EAN codes**

Item	Outer case
WL-CCE/AD-XS	3 701 012 801 155
WL-CCE/AD-SM	3 701 012 802 015
WL-CCE/AD-LXL	3 701 012 801 162